

Plage		Tecumseh	Po (W)	Pabs (W)	COP	Poids (kg)
HP	To=-10°C Tk=45°C DS=10K SR=3K	SH 4576 Z	9 930	4 700	2,13	79
		SH 4591 Z	11 770	5 700	2,08	79
		SH 4610 Z	13 780	6 600	2,09	79
		SH 4612 Z	15 910	7 700	2,08	79
		SH 4615 Z	19 360	8 700	2,22	120
		SH 4620 Z	26 010	11 700	2,21	126
BP	To=-30°C Tk=45°C DS=10K SR=3K	SH 2524 Z	3 340	3 000	1,12	55
		SH 2529 Z	3 850	3 300	1,17	79
		SH 2534 Z	4 840	4 100	1,19	79
		SH 2542 Z	5 940	4 900	1,22	79
		SH 2552 Z	7 080	5 400	1,30	79
		SH 2568 Z	9 790	7 500	1,30	120
SH 2575 Z	10 690	8 000	1,33	130		
Plage		Bitzer	Po (W)	Pabs (W)	COP	Poids (kg)
HP	To=-10°C Tk=45°C DS=10K SR=3K	4EC6.2Y	10 490	5 250	2,00	86
		4DC7.2Y	12 440	6 180	2,01	88,5
		4CC9.2Y	15 200	7 580	2,01	90,5
		4TCS12.2Y	19 550	9 090	2,15	141
		4PCS15.2Y	23 400	10 340	2,26	147
		4NCS20.2Y	27 100	12 300	2,20	150
BP	To=-30°C Tk=45°C DS=10K SR=3K	4EC4.2Y	3 530	3 170	1,11	84
		4DC5.2Y	4 350	3 880	1,12	85,5
		4CC6.2Y	5 330	4 770	1,12	90,5
		4TCS8.2Y	6 700	5 600	1,20	134
		4PCS10.2Y	7 760	6 340	1,22	139
		4NCS12.2Y	9 000	7 450	1,21	141
4I13.2Y	10 800	9 040	1,19	179		
Plage		COPELAND	Po (W)	Pabs (W)	COP	Poids (kg)
HP	To=-10°C Tk=45°C DS=10K SR=3K	D2SA-55X	10 850	5 460	1,99	95
		D2DL-75X	11 850	5 050	2,34	145
		D2DB-75X	14 500	6 220	2,33	145
		D3DA-75X	16 750	7 270	2,30	163
		D3DC-100X	20 100	8 400	2,40	175
		D3DS-150X	26 800	11 750	2,28	178
BP	To=-30°C Tk=45°C DS=10K SR=3K	DLL-30X	2 730	2 390	1,14	91
		DLSG-40X	3 610	3 080	1,13	82
		D2DB-50X	4 880	3 850	1,27	140
		D3DA-50X	5 900	4 740	1,24	157
		D3DC-75X	7 300	5 720	1,27	161
		D3DS-100X	10 150	7 720	1,31	173
D4DF-100X	10 100	8 120	1,25	195		
Plage		DORIN	Po (W)	Pabs (W)	COP	Poids (kg)
HP	To=-10°C Tk=45°C DS=10K SR=3K	H403CC	9 112	4 390	2,08	75
		H503CC	11 187	5 160	2,17	79
		H701CC	13 350	6 360	2,10	92
		H750CC	16 062	7 700	2,09	99
		H801CC	19 212	9 370	2,05	94
		H1500CC	25 418	11 780	2,16	136
BP	To=-30°C Tk=45°C DS=10K SR=3K	H300CS	2 997	2 400	1,25	54
		H390CS	3 907	3 310	1,18	56
		H551CS	5 097	4 040	1,26	91
		H701CS	6 065	4 750	1,28	92
		H751CS	7 260	5 660	1,28	92
		H1000CS	9 968	7 070	1,41	135
H1501CS	11 518	8 280	1,39	132		
Plage		BOCK	Po (W)	Pabs (W)	COP	Poids (kg)
HP	To=-10°C Tk=45°C DS=10K SR=3K	HGX34e/255-4S	10 500	4 890	2,13	96
		HGX34e/315-4S	13 100	6 020	2,16	97
		HGX34e/380-4S	16 100	7 470	2,16	96
		HGX4/465-4S	19 500	9 540	2,04	151
		HGX4/555-4S	23 200	11 100	2,08	153
		HGX4/650-4S	28 500	13 600	2,09	155
BP	To=-30°C Tk=45°C DS=10K SR=3K	HGX34e/215-4	2 560	2 280	1,13	92
		HGX34e/255-4	3 340	2 870	1,16	92
		HGX34e/315-4	5 320	3 580	1,21	94
		HGX34e/380-4	5 420	4 480	1,22	93
		HGX4/465-4	6 740	5 680	1,19	148
		HGX4/555-4	8 210	6 760	1,22	150
HGX4/650-4	9 940	8 330	1,20	152		